

ESTEP 2025 Annual Event

28-30 October 2025
Udine (ITALY)

How decarbonisation, digitisation
and circular solutions forge the
sustainable European steel future?

Jean BORLEE
CRM
Unit Manager ELIMIN



UPSCALING AT CRM

to support EU Iron-&Steelmaking de-carbonization & Circular Economy Roadmaps



DIGIMET



DANIEMI AUTOMATION



**UNIVERSITÀ
DEGLI STUDI
DI UDINE**
HIC SUNT FUTURA

Pre-processing tools




...

• ...

SinByOSe
TRANSinter

COACH

ZincVal
Zhyron



Ironmaking pilots BF & DR

Lab reduction furnace

500 g samples
 Ambient pressure
 Max 1000°C
 ISO 11258:2015 or R180/COREM



HUGE

Batch processing of a fixed bed of granular solids → **40kg DRI**

- Sample : Ø16 cm - height 115 cm
- max 1000°C & 45 bar
- air, O₂, CO, CO₂, CH₄, H₂O, N₂, H₂





RACHEL 2025

55kg DRI – 10 bar N₂, CO₂, H₂, CH₄ & CO

Full grain size distribution 100 NM³/h

Sinter, pellets, CBA 1000°C

Mixed charges 10 bar



H₂transBF
 2030

Safe
 H-DRI

HBI
 C-Flex

Pilot EAF/SAF/Plasma furnace



...


InSGeP

• ...

Direct Reduction reactors

Lab reduction furnace



500 g samples
Ambient pressure
Max 1000°C (1100°C ?)
ISO 11258:2015 or R180/COREM



HUGE

Batch processing of a fixed bed of granular solids → 40kg DRI

- Sample : Ø16 cm - height 115 cm
- max 1000°C (1050°C?) & 45 bar
- air, O₂, CO, CO₂, CH₄, H₂O, N₂, H₂



Lab reduction furnace


- 2 coaxial tubes (sample on grate in inner one)
- Upward gas flow (inner tube)
- Gas is heated as it flows between both tubes
- Preheating to reduction temperature under a nitrogen flow

Input gas : N₂ - CO - CO₂ - H₂ - CH₄

Upcoming

RACHEL

55kg DRI – 10 bar
2 trials / day



MIDREX
ENERGIRON
NG vs H₂




Blast Furnace

Ways and means



On-line Dust counting/sizing

- Pilot + industrial scale



MOGADOR

2-D mathematical model of the blast furnace at steady state (symmetry of revolution)


+ FactSage

Design of instrumented tuyere

- Char movement
- Raceway depth
- Gas chemical analysis
- Raceway Temperature

Liquid levels model

Based on strain gauges measurements



Burden characterisations

Carboneous burden

Cokarac

Coke degradation in the ...
Thermal + mechanical + chemical

Ferrous burden

Standard Tests

- ISO T (2015)
- RDI (2017)
- Reducibility (2017)

HUGE/RACHEL reactors

New shaft simulation trial
Full grain size distribution

Softening trials

Shrinkage under load → Start of softening and start of melting trial.

Viscometer (rheometer)

- Working temperature range: 600 - 1650 °C
- Liquid slag volume : 20 ml



Cold bonded agglomerates

Briquetting



Extrusion

De-airing extruder by Handle (100 l/h)



ELIMIN pyrolysis facilities Alternative reductants



Thermo-conversion Unit - HUGE DR reactor configuration

Variable gas inlet : H_2 , N_2

Variable gas inlet :
 CO , CO_2 , H_2O , O_2

Pre-heater : max 350-400°C but
high flow (10-20Nm³/h)



600-1000°C max

Pre-heating
Balls
~55 cm

Max 950-1000°C
Heating cycle freely
adapted



Pellets
~115 cm
45 kg

H = 1.7m, inner diameter= 16 cm



**MIDREX
ENERGIRON
NG vs H_2**

Gas output + analysis :
 CO , CO_2 , H_2 , O_2 , CH_4 , C_2

- 40 kg DRI
- Weakness = time consuming
→ RACHEL


New reduction pilot reactor **RACHEL**



- **Max 10 bars** = 'easier' to operate
⇔ 2 trials/day
- **Homogeneous 55 kg DRI**
- Integration in existing HUGE infrastructure
- Commissioning S2 2025

BF or DR shafts

Classical & high% H_2
working points



N_2 , CO_2 , H_2 , CH_4 & CO



100 NM^3/h



1000°C




10 bar

BF shaft simulation based on RACHEL reactor

Main features:

- Testing a full mineral layer
 - Height up to 45 cm
 - full grain size distribution and large size particles vs. very narrow grain size and small particles tested in classical lab tests
- Possibility to include mixes of [sinter & pellets + Cold bonded agglomerates]
- Possibility to simulate specific descent path with actual gas composition and flow




Gas injection and reactor temperature regulated to simulate a specific descent path, according to on-site probing or modelling (CRM's Mogador model) → variables in time

DR shaft simulation based on RACHEL reactor

Main features:

- Testing a full mineral layer
 - Height up to 45 cm
 - full grain size distribution and large size particles vs. very narrow grain size and small particles tested in classical lab tests
- Possibility to include mixes [pellets + Cold bonded agglomerates]
- Possibility to simulate specific descent path with actual gas composition and flow




Gas injection and reactor temperature regulated to simulate a specific descent path, according to on-site probing or modelling (CRM's Mogador model) → variables in time

HBI C-Flex Project: Reoxidation behaviour and stability of direct reduced and hot briquetted iron with variable iron and carbon content



 **Start date:** 01.07.2023
 **Duration:** 42 months
 **Budget:** 2.4 Mio. €
 **Coordinator:** K1-MET GmbH
 **Contact:** info@hbi-c-flex.eu
 **Website:** www.hbi-c-flex.eu




Supportive Advisory Board




Goals and expected results of HBI C-Flex

- Contribution to the decarbonisation of the steel industry
- Support the use of **hydrogen-based direct reduction**
- Examine the influences on HBI production
- Determination of **HBI reoxidation and reactivity** and strategies to avoid reoxidation
- Definition of strategies for **safe handling and onsite storage**
- Scientific basis for extending IMSBC Code to cover zero-carbon HBI
- Contribution to new, sustainable and low-carbon steelmaking materials



Follow HBI C-Flex on LinkedIn



Safe-HDRI



✓ CRM Contact persons =
Frederic.vanloo@crmgroup.be
Damien.garot@crmgroup.be



Topic : Safe transport of DRI from H₂-based direct reduction considering quality-related H-DRI reactivity, stability, the efficiency of **passivation methods** and health and recycling aspects

- H₂-based direct reduction : ≠ iron ore qualities and conditions (pure H₂ and mixed with NH₃).
- H-DRI reoxidation : external and internal transport/storage + efficiency of passivation methods → to design a safe H-DRI transport system.
- Reuse of H-DRI fines produced during handling
- updated transport system standardization and extend existing or new transport guidelines.
- ❖ **Project Start : Oct'24 – Kick-off meeting in Leoben 8-9 Oct'24**

CRM contributions :

- **WP2** - Production of H-DRI with different qualities
 - Lab furnace - 500 g
 - HUGE/RACHEL reactor ~ 50kg
- **WP3** - Characterisations of input / output materials


+ Supported by letters of interest a.o.
 ESTEP, Worldsteel, Eurofer, IIMA. ASMET, Erdemir, VDEh,
 Federacciai

Partner	RTO / industrial	Country
K1-Met	RTO	Austria
ADI	Industrial	Italy
AM III	RTO	Spain
AM Mz	RTO	France
BFI	RTO	Germany
CRM	RTO	Belgium
Danieli	Industrial	Italy
DB cargo Aktiengesellschaft	Industrial	Germany
Dillinger	Industrial	Germany
HKM	Industrial	Germany
Innofreight Solution	Industrial	Austria
Innofreight Germany	Industrial	Germany
Univ Leoben	University	Austria
RINA	RTO	Italy
Tata Steel NL tech.	RTO	Netherlands
Univ. Salento	University	Italy
Voestalpine Stahl	Industrial	Austria
Voestalpine Stahl Donawitz	Industrial	Austria


Optical microscopy : application for Ironmaking

Burden characterisation – **Quantitative + Qualitative** analysis

- Metallization degree determination by Optical Image Analysis (OIA)




- Optical images
- 500x magnification



- RGB images
- Image segmentation



- Fe metal
- Fe oxide
- Silicates + resin + pores



Quantification of phases pellet diameter



Analyse pellet



Briquette's before reduction with "pathways" highlighted and reduced briquette with cracks generated.

Low CO₂ BF route


Sintering

Waste Gas Recirculation

- Support to plants
- VeLoSint process



TACOS RFCs



- Fuel gas injection
- Alternative Solid Fuels
- (New) By-products management

SinByOSe RFCs

New 2023 :

- Sinter for DR process
- DR on sinter strands

TRANSiner RFCs

Blast furnace

Cold-bonded agglomerates (By-products & fine ores)


→ No sintering/pelletizing step necessary anymore

COACH RFCs

Alternative Reductants

H₂-rich gas injection at tuyere / lower shaft level and DRI (HBI) charging at BF

H2TRANSBF RFCs



- Shaft gas injection to optimise gas utilisation and temperature zones
 - DRI/HBI to reduce energy demand and coke layer height
 - DRI/HBI + hydrogen to increase permeability (DRI/HBI: material stability, hydrogen: gas viscosity/density)
 - Coke oven gas, Syngas, fossil free methanol to reduce share of carbon based reduction

Alternative Reductants

Characterisation and pyrolysis tests of various mixed waste materials for assessment of their suitability for torrefaction, for gasification and for cokemaking



Scrap

Scrap pre-treatment: Thermal pre-conditioning furnace



CAESAR (Circularity Enhancements by Low quality Scrap Analysis and Refinement) HEU project: Industrial demonstration of scrap sorting/cleaning based on innovative combination of best available technologies.

CAESAR HEU

H₂transBF 2030

RFCS funded project



Proposal overview :

Title : Minimisation of CO₂ Emissions from the BF by hydrogen containing injectants and use of DRI/HBI during transition to new Ironmaking processes until 2030

Objectives :

The target = 25-35% CO₂ reduction, using synergies from the increasing availability of H₂, H₂-rich injectants and DRI/HBI.

Consortium


BFI (De) - Coordinator
CRM (Be)
AMMR (Fe)
Tata Steel (NL)
Dillinger (De)
HKM (De)
ABO (FI)
Oulu (FI)
PW (Lu)
Swerim (Se)

Duration

42 months

CRM Contact

R .Rabani





Mogador

Mogador = good compromise : all aspects of the BF simulated (some in a simplified way) with a low calculation time (~ 20 min for high resolution on a 'classical laptop').

MOGADOR – State-of-the-art numerical 'MOdel for GAs Distribution and Ore Reduction'


In 1995, CRM started the development of a 2-D mathematical model of the blast furnace at steady state (symmetry of revolution)

- ❑ Industrial validation at Arcelor Mittal Gent (2001)
- ❑ Industrial use of Mogador :
 - to help BF operators choosing the proper burden distribution pattern vs desired effect on BF results
 - to follow up evolution of cohesive zone (soft sensing)
 - Support to BF relining : optimal inner shape for maximized productivity



- Modification of the cohesive zone resulting of a slight charging pattern modification.


Evolution of the cohesive zone




2025 Typical results in a BF




Components of gas phase



Gas flow field



Gas-solid temperature field



For a better future